Countermeasure	Prioritization Criteria
Roundabout	<ul> <li>Required: Unsignalized intersection with a history of severe (K</li> </ul>
	A, or B) angle, left turn, and/or pedestrian crashes.
	<ul> <li>One point for every target crash of KAB severity.</li> </ul>
	<ul> <li>One point if four or more legs are present at the intersection.</li> </ul>
	<ul> <li>One point if rural.</li> </ul>
	<ul> <li>One point for every 10 degrees of skew angle.</li> </ul>
Mini Roundabout	<ul> <li>Required: Unsignalized intersection with a history of angle,</li> </ul>
	left turn, and/or pedestrian crashes.
	<ul> <li>Intersections with lower daily volumes and less available</li> </ul>
	ROW.
	<ul> <li>One point for every target crash of KAB severity.</li> </ul>
	<ul> <li>Two points if approach speed limits are 35 MPH or less.</li> </ul>
	<ul> <li>One point for every local approach.</li> </ul>
	<ul> <li>One point if four or more legs are present at the intersection.</li> </ul>
	<ul> <li>One point if urban.</li> </ul>
All-Way Stop-	<ul> <li>Required: Minor stop control or uncontrolled intersection with</li> </ul>
Control	a history of angle, left turn, pedestrian, and/or bicyclist
	crashes.
	<ul> <li>One point for every target crash of KAB severity.</li> </ul>
	<ul> <li>Three points if difference between major and minor road</li> </ul>
	AADT is less than 100, two points if the difference is between
	100 and 250, and one point if the difference is between 250
	and 500.
Intersection	<ul> <li>Required: Intersection with a history of nighttime crashes in</li> </ul>
Lighting	unlit conditions, especially involving pedestrians.
	<ul> <li>One point for every nighttime crash.</li> </ul>
	<ul> <li>One point for every pedestrian crash.</li> </ul>
	<ul> <li>One point for every 10 degrees of skew angle.</li> </ul>
	<ul> <li>One point if major road AADT exceeds 3,000.</li> </ul>
	<ul> <li>One point if minor road AADT exceeds 1,500.</li> </ul>
	<ul> <li>One point if major road posted speed limit exceeds 45 mph.</li> </ul>
	<ul> <li>One point if minor road posted speed limit exceeds 45 mph.</li> </ul>
Dedicated Turn	Required: Intersection with a history of crashes related to left
Lane	or right turns where a dedicated turn lane is not currently
	present.
	<ul> <li>One point for every target crash of KAB severity.</li> </ul>
	<ul> <li>One point if no lighting is present.</li> </ul>
	<ul> <li>One point if major approach speed limit exceeds 35 MPH.</li> </ul>
	<ul> <li>One point if major road AADT exceeds 10,000.</li> </ul>

Raised Crosswalk (only applicable for local road approaches	<ul> <li>Required: Intersection with a history of pedestrian crashes and the intersecting roads are local or collector streets with existing sidewalks.</li> </ul>
outside of State ROW)	One point if a pedestrian crash has occurred.
	<ul> <li>Two points if a pedestrian crash occurred "in a marked crosswalk".</li> </ul>
	<ul> <li>One point if lighting is present.</li> </ul>
	<ul> <li>One point if posted speed limit on minor approach is less than or equal to 30 MPH.</li> </ul>
	<ul> <li>One point if minor road has two through lanes.</li> </ul>
High-Friction	Required: Intersection or its approaches with a history or
Surface Treatment	evidence of friction issues.
(HFST)	<ul> <li>One point for every target crash of KAB severity.</li> </ul>
	<ul> <li>One point for every wet road crash.</li> </ul>
	<ul> <li>One point if major road speed limit is at least 45 mph.</li> </ul>
<b>Protected Bicycle</b>	<ul> <li>Required: Intersection or its approaches with existing bicycle</li> </ul>
Lanes with Bike	lanes and a history of bicycle-related crashes.
<b>Boxes and Bike</b>	<ul> <li>One point for every bicycle crash.</li> </ul>
Signals	<ul> <li>One point if no lighting is present.</li> </ul>
	<ul> <li>One point if transit stop is present within quarter mile.</li> </ul>
	<ul> <li>One point if intersection has 4 or more legs.</li> </ul>